

IST 32-62 N-DIGIT


SMALL SIZE,
UNBEATABLE EFFICIENCY



Typical application
30 to 240 l /24 h



Static
oil



Small
size



Touch Screen
& PLC



Manual
functioning



Easy to use



Installation: NON-CLASSIFIED AREA

THE BENEFITS OF THE IST SERIES

Practicality

- easy sludge removal thanks to a handy tilt function and practical waste bags
- immediate regulation of the heating temperature and cycle time on the digital control panel

Versatility

- tank capacities available from 15 to 60 litres
- a vast range of useful accessories is available, including a solvent loading kit, distillate tank and sight glasses

Reproducibility

- precise control with integrated visual display of distillation parameters
- alarm with message on display for process anomalies which require a service response

IST series distillers with a load capacity of 30 to 60 litres are the ideal solution for small and medium sized businesses which require a high quality, safe and flexible **distillation unit to handle constant repeated solvent loads**. The powder coated steel structure guarantees a **long service life** even in heavy duty applications.

The IST 32 and IST 62 regenerators, designed for applications with a moderate solvent consumption, represent the state of the art in small industrial distillation units: they offer **highly efficient** distillation with **excellent sludge concentration** and **reduced energy consumption**. All cycle parameters, including process temperatures, are monitored by the PLC and can be viewed in real time. Distillation units in this range run a software which is similar to that used on larger unit, with a vast range of functions.

Model	Installed power	Loading capacity	Productivity l/24h
IST 32	2.6 kW	30 l	30 to 180
IST 62	4.5 kW	62 l	60 to 240

IST 32-62

ATEX II2G


SMALL SIZE,
UNBEATABLE EFFICIENCY



Typical application
30 to 240 l / 24 h



Static
oil



Small
size



Touch Screen
& PLC



Manual
functioning



Easy to use

IST series distillers with a load capacity of 30 to 60 litres are the ideal solution for small and medium sized businesses which require a high quality, safe and flexible **distillation unit to handle constant repeated solvent loads**. The powder coated steel structure guarantees a **long service life** even in heavy duty applications.

The IST 32 and IST 62 regenerators, designed for applications with a moderate solvent consumption, represent the state of the art in small industrial distillation units: they offer **highly efficient** distillation with **excellent sludge concentration and reduced energy consumption**. All cycle parameters, including process temperatures, are monitored by the PLC and can be viewed in real time. On machine classified for Zone 1, the PLC is protected by an explosion proof housing. Distillation units in this range run a software which is similar to that used on larger unit, with a vast range of functions.

THE BENEFITS OF THE IST SERIES

Practicality

- easy sludge removal thanks to a handy tilt function and practical waste bags
- immediate regulation of the heating temperature and cycle time on the digital control panel

Versatility

- tank capacities available from 15 to 60 litres
- a vast range of useful accessories is available, including a solvent loading kit, distillate tank and sight glasses

Reproducibility

- precise control with integrated visual display of distillation parameters
- alarm with message on display for process anomalies which require a service response

Model	Installed power	Loading capacity	Productivity l/24h
IST 32	2.6 kW	30 l	30 to 180
IST 62	4.5 kW	62 l	60 to 240